



- Safety liner for your protection
- Custom insulation designed for maximum field flexibility
- Sequentially marked cable available
- Custom imprinted cable available with quick turnaround
- Highly flexible soft annealed #30 copper stranding
- Oil, water, sunlight resistant
- Assemblies are UL Recognized

**CONSTRUCTION:**

Highly flexible stranded No. 30 bare copper conductor insulated with high grade TPE and then jacketed with durable TPE. A high strength fiber braid is added between the insulation and the jacket providing extra strength. Operating temperatures range from -40°C to 90°C dry and 75°C wet. Rated voltage up to 2000V.

**APPLICATION:**

Available with male and female CAM-LOKs cut to any length. Open ended with bare copper or pin and sleeve.

**For information on additional specifications or custom assemblies, call 1-800-233-3848.**

PART NO.	DESCRIPTION	RATING	LENGTH	CABLE	CONNECTOR	CONNECTOR
TW0110	4/0 TW BLK W/ BLK M CAM & BARE	405 AMP, 2000V	3'	TYPE W	4/0 M CONNECTOR	BARE WIRE
TW0111	4/0 TW BLK W/ BLK F CAM & BARE	405 AMP, 2000V	3'	TYPE W	4/0 F CONNECTOR	BARE WIRE
TW0266	4/0 TW BLK W/ BLK M CAM & LUG	405 AMP, 2000V	3'	TYPE W	4/0 M CONNECTOR	4/0 LUG
TW0112	4/0 TW BLK W/ BLK F CAM & LUG	405 AMP, 2000V	3'	TYPE W	4/0 F CONNECTOR	4/0 LUG
TW0339	4/0 TW BLK W/ BLK M CAM & PIN	405 AMP, 2000V	3'	TYPE W	4/0 M CONNECTOR	PIN
TW0344	4/0 TW BLK W/ BLK F CAM & PIN	405 AMP, 2000V	3'	TYPE W	4/0 F CONNECTOR	PIN

**DIRECT WIRE & CABLE INC.**

412 Oak Street, Denver, PA 17517 P 1 800 233 3848 F 1 800 752 2654

Warehouse Locations – Chicago IL, Houston TX, Portland OR, Los Angeles CA

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

Made in USA  
www.directwireusa.com