

**12/3 GFCI CORDS**



- Rugged jacket
- Flexible
- Resists Abrasion, Grease, Oil and Water
- Unbreakable, molded-on connectors
- Every cord is tested
- Indoor/outdoor use
- Contractor approved
- Meets all UL & OSHA requirements
- Made in the USA

**CONSTRUCTION:**

Highly flexible annealed 30 gauge bare copper conductors, insulated with a vinyl SJTW jacket. Operating temperatures range from -37 °C to +91°C (-35°F to +195°F). The 12 gauge, 3 conductors are rated at 125V, 15A, (1875W).

| PART #        | DESCRIPTION      | AMPS | VOLTS | WATTS | LENGTH |
|---------------|------------------|------|-------|-------|--------|
| 4021230002510 | TRI TAP GFCI     | 15A  | 120V  | 1800W | 2 ft.  |
| 4021230002520 | TRI TAP GFCI 90° | 15A  | 120V  | 1800W | 2 ft.  |
| 4021230006900 | QUAD BOX GFCI    | 15A  | 125V  | 1875W | 6 ft.  |

**APPLICATION:**

Designed for construction sites. Ideal for industrial applications, marinas, etc.

**DIRECT WIRE & CABLE INC.**

412 Oak Street, Denver, PA 17517 P 1 800 233 3848 F 1 800 752 2654

Warehouse Locations – Chicago IL, Houston TX, Portland OR, Los Angeles CA

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

Made in USA  
www.directwireusa.com