

PRE-ASSEMBLED: LEADS, GROUNDS AND STINGERS/WHIPS



Lead



Ground



Stinger/Whip

Save Time, Labor and Money

- Rugged jacket
- Flexible
- Stock Colors (Blue, Green, Red, Yellow) available
- Resists Abrasion, Cut, Tear, Flame, Grease, Oil and Water
- Stocked with Lenco and Tweco Connectors
- Cable made in the USA

CONSTRUCTION:

Offered with all of our highly flexible standard welding cable products. Available in black, blue, green, red and yellow jacket colors. Also available on 250, 500, and 1,000 ft. reels. Coiled, boxed and shrink wrap packaging available for 25, 50 or 100 ft. lengths. Custom lengths also available upon request. **Custom indent or standard printing available. Inquire about stocked colors and gauges.**

APPLICATION:

Designed to offer your customers ready to weld leads, grounds and stinger/whips. Saves time and labor cost, while improving the finished assembly quality.

FLEX-A-PRENE CABLE SPECIFICATIONS

GAUGE	STRANDING	O.D	AVG. WALL	WEIGHT/1,000 ft.	RESISTANCE Ohms/1,000 ft.
#6	259/.010	.318	.060	112 lbs.	.417
#4	378/.010	.358	.060	154 lbs.	.286
#2	623/.010	.422	.060	238 lbs.	.174
#1	777/.010	.503	.080	310 lbs.	.139
1/0	988/.010	.538	.080	384 lbs.	.110
2/0	1235/.010	.591	.080	470 lbs.	.088
3/0	1539/.010	.630	.080	576 lbs.	.071
4/0	2014/.010	.710	.080	734 lbs.	.054

SUGGESTED AMPACITY FOR WELDING CABLE

GAUGE	50'	75'	100'	125'	150'	175'	200'	225'	250'	300'	350'
#4	100	100									
#3	150										
#2	200	150	100	100							
#1	²⁵⁰ / ₃₀₀	200	150	150	100						
1/0	350	250	200	150	150	100	100				
2/0	⁴⁰⁰ / ₄₅₀	300	250	200	150	150	100	100			
3/0	500	³⁵⁰ / ₄₀₀	300	250	200	150	150			100	
4/0	⁵⁵⁰ / ₆₀₀	⁴⁵⁰ / ₅₀₀	³⁵⁰ / ₄₀₀	300	250	200	200	150	150		100

DIRECT WIRE & CABLE INC.

412 Oak Street, P.O. Box 57 Denver, PA 17517 P 1 800 233 3848 F 1 800 752 2654

Warehouse Locations – Chicago IL, Houston TX, Portland OR, Reno NV

Specifications contained herein reflect current data and are subject to change. Values are nominal and or approximate.

Made in USA
www.directwireusa.com