



Veri-Flex Stage Cable

Type Stage Cable is used primarily in the entertainment industry, including motion picture, television, theatre and stage lighting. Also applicable for rental, mining, and temporary power.

- UL Listed E471601
- UL Listed 1680
- Resists Abrasion, Cut, Tear, Ozone, Flame, Grease, Water, Acid, Diesel, and Gas
- Oil and Sunlight Resistant as per UL 2556
- MSHA P-07-KA160003
- FT-5 and VW-1 flame test
- RoHS Compliant
- CSA C22.2 No 96
- Made in the USA



CONSTRUCTION:

Flexible industrial grade 30 gauge annealed copper

INSULATION

Proprietary EPDM insulation and CPE jacket

TEMP RANGE

105° C Dry / 75° C Wet

Stock Sizes

Available in 250 and 500 ft reels

Packaging

Coiled, boxed, banded, and shrink wrap

COLORS

Available in black, red, green, blue, yellow, brown, white, and orange

Cable Options

Custom extruded stripe, indent, surface print, and logos





CONSTRUCTION

GAUGE	STRANDING	O.D.	AMPACITY	WEIGHT/1,000ft.
#8	168/30	0.268	80	110
#6	266/30	0.313	105	150
#4	429/30	0.358	140	209
#2	676/30	0.435	190	299
#1	845/30	0.468	220	358
1/0	1066/30	0.510	260	443
2/0	1339/30	0.562	300	545
3/0	1677/30	0.600	350	654
4/0	2109/30	0.678	402	807



412 OAK STREET
DENVER, PA 17517

(800) 233-3848

www.directwireusa.com